

ASPECT GLASS LUMINAIRE

DELRAY
LIGHTING
INCORPORATED

2
3
4



TYPE:

PROJECT:

ORDER NUMBER:

Model#	Paint Finish	Glass Color	Wattage	Voltage	Ballast
	H ammertone	I ndigo	18, 26,	1 -120V	E -Electronic
	S ilver	M arine	32, 42	2 -277V	D5, D8,
	W hite	O pal			D9 -Dimming
	CC -Custom	T angerine			only for items
	RAL color	WA -White			marked \blacklozenge .
		Acrylic			(See back page
					for details.)

Example:


2342	W	M	32	1	E
------	---	---	----	---	---

ARMATURE

Suspends from cable or rod, is constructed of extruded aluminum, and is securely fastened to cast wire way top. Ballast fits inside extruded cylinder attached to lamp holder for pulldown access. U.L. listed for damp locations.

2340

Fluorescent




SURFACE MOUNT

Steel canopy mounts to all recessed J-boxes. Ballast fits inside extruded cylinder **2341** or horizontally in flat canopy **2345**. Specify **EM** for emergency battery pack, available on **2341** only. The 650 lumen battery pack adds 9 3/4" to canopy height, 13 3/4" with the 1300 lumen unit. U.L. listed for damp locations.


2341

Fluorescent



2345 \blacklozenge

Fluorescent




PENDANT MOUNT

Canopies mount to standard J-boxes. Ballast fits inside extruded cylinder **2342** or horizontally in flat canopy **2347**. Pendant is 6' standard or can be specified in any length with 12' max for CFL (3' max. dimming). Specify **EM** for emergency battery pack, available on **2342** only. The 650 lumen battery pack adds 9 3/4" to canopy height, 13 3/4" with the 1300 lumen unit. U.L. listed for damp locations.


2342

Fluorescent



2347 \blacklozenge

Fluorescent




WALL MOUNT

4" square by 3/16" thick aluminum wall plate mounts to 3" mudring on 2 3/4" vertical, centered holes. Fixture connects to extruded aluminum arm, which is securely fastened to cast wire way top. Ballast fits inside extruded cylinder **2343** or horizontally in flat canopy **2344**. U.L. listed for damp locations.


2343

Fluorescent



2344 \blacklozenge


Fluorescent




BURBANK,
CALIFORNIA,
91505
WWW.
DELRAY
LIGHTING.
COM

FLUORESCENT

1-32W PLT



CP DISTRIBUTION



COEFFICIENTS

% CEILING 80 (20% FLOOR)

% WALL	70	50	30
0	96	96	96
1	85	80	76
2	77	69	63
3	70	61	54
4	64	54	46
5	59	48	40
6	54	43	35
7	50	38	31
8	46	34	27
9	43	31	24
10	39	28	21

NOTES

234232

1-32W triple tube
G24q-3 electronic socket
Total lumens: 2400
Spacing criteria: 1.7


BALLAST INFO

DIMMING

- Dimming only available for items marked **◆** on page 1.
- Max. 3' pendant length.
- Voltage *must* be specified.
- Controls lumen output down to $\pm 5\%$.
- Compatible dimmers required for all ballasts.
- **D5** Advance Mark VII for 18, 26, 32 or 42W lamp.
- **D8** Lutron Hi-Lume 1% for 26 or 32W lamp. Controls lumen output down to $\pm 1\%$.
- **D9** Lutron EcoSystem for 18, 26, 32 or 42W lamp. Controls lumen output down to $\pm 5\%$.

EMERGENCY


- Voltage *must* be specified.
- **EM** emergency power provides 650 lumens for one lamp for 90 minutes. Ht.=15.25"
- **EM13** emergency power provides 1300 lumens for one lamp for 90 minutes. Ht.=18.75"



WALL MOUNTING

WALL PREPARATION

- For model 2343.
- Mount holes must be aligned vertical center, as shown:



2349 ARM EXTENSION

- Specify arm length, up to 36" maximum.
Example: **2349X** (X=length)
- Aircraft cable, grip locks and mounting hardware included.

