

ASPECT REFLECTOR WITH UP-LIGHT



TYPE:

PROJECT:

ORDER NUMBER:

Model#	Paint Finish*	Wattage	Voltage	Ballast
	Hammertone	18, 26, 32,	1-120V	E-Electronic
	Silver	42 or 57	2-277V	EM
	White			EM13
	CC-Custom			
	RAL color			

(See back page for details.
For dimming, see model 271.)

Example:

2792	W	32	1	E
------	---	----	---	---

*Paint finish on ballast housing and ceiling canopy only.
Reflector exterior is matte anodized aluminum.


**DELRAY
LIGHTING
INCORPORATED**

279


PENDANT MOUNT

Canopy mounts to standard J-boxes with 6' of Pendant standard and can be specified in any length. U.L. listed for damp locations.

2792
CFL




2792EM
CFL



SURFACE MOUNT

Canopy mounts to standard J-boxes and supports ballast housing. U.L. listed for damp locations.

2791
CFL



REFLECTORS

Aluminum clad top reflector has frosted glass top for ambient up-lighting and an internal downlight reflector for beam and glare control.

Note: Reflector cannot be custom painted due to anodized finish.


BURBANK,
CALIFORNIA,
91505
WWW.
DELRAY
LIGHTING.
COM

COMPACT FLUORESCENT


BALLAST INFO

OPTIONS

1-32W PLT



CP DISTRIBUTION



COEFFICIENTS OF UTILIZATION

% CEILING 80 (20% FLOOR)

% WALL	70	50	30
0	78	78	78
1	74	72	70
2	70	67	64
3	67	62	59
4	63	58	55
5	60	54	50
6	57	51	47
7	53	47	43
8	51	44	40
9	48	41	37
10	45	39	35

NOTES

279232

1-32W triple tube
 G24q-2 electronic socket
 Total lumens: 2400
 Spacing criteria: .8

EMERGENCY

- Voltage *must* be specified.
- **EM** emergency power provides 650 lumens for one lamp for 90 minutes. Ht.=15.25"
- **EM13** emergency power provides 1300 lumens for one lamp for 90 minutes. Ht.=18.75"

AL-Acrylic Lens. For security and food service installations.
 Use with CFL lamps *only*.

