

KONE FROST GLASS PENDANT LUMINAIRE



TYPE:

PROJECT:

ORDER NUMBER:

Model#	Wattage	Voltage
	13, 18, 26	1-120V
	or 32	2-277V

Example:

6010	26	1
------	----	---


DELRAY
LIGHTING
INCORPORATED

6010

KONE OPAL PENDANT

Canopy mounts to standard J-box. Electronic ballast fits inside fixture for easy access. Pendant is 6' standard, with steel braided power cord. Finish is silver powder coat. Glass shade is translucent frost. Fixtures have a twist lock socket for secure, easy relamping. Dimming and emergency battery backup are not available. U.L. Listed for damp locations.

6010
Fluorescent



BURBANK,
CALIFORNIA,
91505
WWW.
DELRAY
LIGHTING.
COM

JULY 2008

FLUORESCENT


BALLAST INFO

1-32W PLT



- Standard in universal voltage 120V through 277V.
- .98 power factor with THD<10%.
- End of lamp life protection.

CP DISTRIBUTION



COEFFICIENTS OF UTILIZATION

% CEILING 80 (20% FLOOR)

% WALL	70	50	30
0	96	96	96
1	85	80	76
2	77	69	63
3	70	61	54
4	64	54	46
5	59	48	40
6	54	43	35
7	50	38	31
8	46	34	27
9	43	31	24
10	39	28	21

NOTES

6010.32

1-32W triple tube

G24q-3 electronic twist lock socket

Total lumens: 2400

Spacing criteria: 1.7