

## 8" CYLINDER WALL MOUNT LED DOWNLIGHT



Clear Alzak® Haze

**TYPE:**

**PROJECT:**

**ORDER NUMBER:**

Model#	Watts	LEDs	Paint Finish	Options
<b>CLW8</b>	<b>2</b> -21W, 2000 lumens	<b>W30</b> <b>W35</b> <b>W41</b>	<b>BM</b> -Brushed Metal <b>BZ</b> -Bronze <b>K</b> -Carbide Black <b>W</b> -White <b>S</b> -Silver <b>CC</b> -Custom Color*	<b>D11</b>

**Example:**

CLW8	2	35	BM	D11
------	---	----	----	-----

\*Specify RAL color number: \_\_\_\_\_

### SPECIFICATION INFORMATION

#### CYLINDER HOUSING

Constructed of seamless extruded aluminum, with a powder coat finish. Fixture mounts to standard J-box.

#### REFLECTOR

Reflector is anodized, specular, durable and anti-iridescent; available in 30° cutoff (.30). Finish is Clear Alzak® Haze.

#### LED DRIVERS

- Standard drivers are constant current, universal voltage, with 0-10V dimming to 1%.
- Standard and dimming drivers mounted inside canopy.
- Mounts to all standard J-boxes.
- cU.L. listed for damp locations.

#### LEDs

- CREE® LMH LED modules feature opal diffusers that provide the appearance of an A-lamp from below.
- 21W/2000 Lumen.
- 90 CRI
- 50,000 hour LED life

Specify LED color:

- W30**-White (3000° K)
- W35**-White (3500° K)
- W41**-White (4100° K)

#### DIMMING


- **D**-standard supplied driver. Programmable, 0-10V, 120/277V, 50/60 Hz, 1% dimming.
- **D11**-Lutron EcoSystem, LDE14 Series. Dims to 1%. Fade to off.

#### FINISHES

- BM**-Brushed Metal
- BZ**-Bronze
- K**-Black
- W**-White
- S**-Silver
- CC**-Custom Color (Must specify RAL color number.)

#### CLW8

LED  
21 watts  
2,000 lumens



**DELRAY**  
**LIGHTING**  
INCORPORATED


**CLW8**

BURBANK,  
CALIFORNIA,  
91505  
WWW.  
DELRAY  
LIGHTING.  
COM


SEPT 2018

## CLEAR ALZAK 30°

CLW8



## CP DISTRIBUTION



## COEFFICIENTS

### % CEILING 80 (20% FLOOR)

% WALL	70	50	30
0	119	119	119
1	114	111	109
2	108	103	100
3	103	97	92
4	98	91	85
5	93	85	79
6	89	80	74
7	85	76	70
8	81	72	66
9	77	68	62
10	74	64	59

## NOTES

### CLW8121

21W  
 Total lumens: 1468  
 Spacing criteria: 0.78  
 Total luminaire efficiency: 56.3%  
 Clear Alzak x.90

## CLW8100

These LED luminaires that provide conventional footcandle levels  $\leq 1.4\text{W}/\text{FT}^2$ .

CREE® LMH LED modules feature opal diffusers that provide the appearance of an A-lamp from below, and are available in three white color temperatures: **W30** (3000° K), **W35** (3500° K), and **W41** (4100° K); matching the traditional CCT of existing incandescent, fluorescent, and metal halide lamps.

cUL rated for dry locations only.

## LM-79 TEST SUMMARY - CLW8121.W35

Driver:	ERP
Total Lumens:	1468
Input Power (W):	25.5
Efficacy:	56.3
Color Rendering Index (CRI):	91

## OPTIONS

### DIMMING

- **D**—standard supplied driver. Programmable, 0–10V, 120/277V, 50/60 Hz, 1% dimming.
- **D11**—Lutron EcoSystem, LDE14 Series. Dims to 1%. Fade to off.