

8" CYLINDER WALL MOUNT LED DOWNLIGHT



Clear Alzak® Haze

TYPE:

PROJECT:

ORDER NUMBER:

Model#	Watts	LEDs	Paint Finish	Options
CLW8	2 -21W, 2000 lumens	W30 W35 W41	BM -Brushed Metal BZ -Bronze K -Carbide Black W -White S -Silver CC -Custom Color*	D1 D9A D11

Example:

CLW8	2	35	BM	D1
------	---	----	----	----

*Specify RAL color number: _____

SPECIFICATION INFORMATION

CYLINDER HOUSING

Constructed of seamless extruded aluminum, with a powder coat finish. Fixture mounts to standard J-box.

REFLECTOR

Reflector is anodized, specular, durable and anti-iridescent; available in 30° cutoff (.30). Finish is Clear Alzak® Haze.

LED DRIVERS

- Standard drivers are constant current, universal voltage, with 0-10V dimming to 15%.
- Standard and dimming drivers mounted inside canopy.
- Mounts to all standard J-boxes.
- cU.L. listed for damp locations.

A-LINE LEDs

- CREE® LMH LED modules feature opal diffusers that provide the appearance of an A-lamp from below.
- 21W/2000 Lumen.
- 90 CRI
- Dimming available for both wattages and all color temperatures.
- 50,000 hour LED life
- 5-year LED warranty

Specify LED color:

- W30**-White (3000° K)
- W35**-White (3500° K)
- W41**-White (4100° K)

DIMMING

Energy management dimming to 15%, 0-10V, standard. (See back page for details.)


- **D1**-dims to 1%
- **D4A**-Lutron HiLume A Series 2-wire Fwd Phase. *120V only.*
- **D9A**-HiLume A Series Ecosystem 3-wire **L3DA4U1UK**, *120/277V.*
- **D11**-Lutron EcoSystem H-Series **LDE14U1UK** LED driver (≤1%). Purple/purple-gray wire control.

FINISHES

- BM**-Brushed Metal
- BZ**-Bronze
- K**-Black
- W**-White
- S**-Silver
- CC**-Custom Color (Must specify RAL color number.)

CLW8

LED
21 watts
2,000 lumens



DELRAY
LIGHTING
INCORPORATED

CLW8


A-Line LED

BURBANK,
CALIFORNIA,
91505
WWW.
DELRAY
LIGHTING.
COM


MAR 2017

CLEAR ALZAK 30°

CLW8



CP DISTRIBUTION



COEFFICIENTS

% CEILING 80 (20% FLOOR)			
% WALL	70	50	30
0	119	119	119
1	114	111	109
2	108	103	100
3	103	97	92
4	98	91	85
5	93	85	79
6	89	80	74
7	85	76	70
8	81	72	66
9	77	68	62
10	74	64	59

NOTES

CLW8121

21W
 Total lumens: 1468
 Spacing criteria: 0.78
 Total luminaire efficiency: 56.3%
 Clear Alzak x.90

CLW8100

These LED luminaires that provide conventional footcandle levels $\leq 1.4\text{W}/\text{FT}^2$. CREE® LMH LED modules feature opal diffusers that provide the appearance of an A-lamp from below, and are available in three white color temperatures: **W30** (3000° K), **W35** (3500° K), and **W41** (4100° K); matching the traditional CCT of existing incandescent, fluorescent, and metal halide lamps. cUL rated for dry locations only.

LM-79 TEST SUMMARY - CLW8121.W35

Driver:	ERP
Total Lumens:	1468
Input Power (W):	25.5
Efficacy:	56.3
Color Rendering Index (CRI):	91

OPTIONS

DIMMING

Energy management dimming to 15%, 0–10V, standard.

- **D1**—dims to 1% and may be used with incandescent dimmers or with 0–10V purple/gray wires.
- **D9A**—HiLume A Series Ecosystem 3-wire **L3DA4U1UK**, 120/277V.
- **D11**—Lutron EcoSystem H-Series **LDE14U1UK** LED driver ($\leq 1\%$). Purple/purple-gray wire control.