


DOS CIRCULAR DIRECT/INDIRECT WHITE LED WITH OPAL ACRYLIC LENS

DELRAY
LIGHTING
INCORPORATED

DOS LED 6'+8' CIRCLES



TYPE:

PROJECT:

ORDER NUMBER:

Model#	Finish	LEDs	Mount	Option	Option
UDC6 —6 ft.	S —Silver	W30	S —Separate	BDIM-W9	SS
UDC8 —8 ft.	W —White	W35	SR —Sep. Remote	BDIM-W11	
	K —Black	W40	CS —Cen. Standard	BDMXMOD	
		Red	CR —Cen. Remote		
		Blue	NCR —Nexus CR		
		SQ —RGB	SREM —Separate EM		
			CREM —Central EM		

CONSTRUCTION

- Extruded aluminum outer housing with direct/indirect white frosted acrylic diffuser. Shipped in two sections, with joiners for assembly in the field. Each section includes one 8 ft. gray or white 18 AWG adjustable power cord, plus two AC cables with push button grippers. Specify **XP** for additional length (25 ft. max.).

WHITE LEDs

- Nichia Corp. NFSL757 tight bin chips on aluminum clad boards. 90 CRI.
- **W30** (3000K), **W35** (3500K), and **W40** (4000K) white color temperatures.
- Drivers are programmable constant current, 0–10V, 1% dimming, standard.
- Separate switching, order **SS**.

CUSTOM LUMEN OUTPUT REDUCTION

- Factory set custom reduced-lumen output driver configuration. Order **XL**. Specify lumens.

COLOR LEDs

- **Red**, **Blue** or **SQ**—RGB flexible 5050 tapelights.
- Constant voltage drivers are 12V for single color, 24V for RGB sequencer.
- RGB sequencer requires **BDMXMOD** DMX 512 interface.
- Optional DMX wall box control offered separately (see Traxon, page 2.)

STANDARD CANOPY



- Mounts to all standard JBoxes.
- Drivers and DMX module inside surface mount canopy. For remote driver installation, see page 2.
- Specify:
 - S**, **CS**—Standard (10" x 2.25")
 - SR**, **CR**, **NCR**—Remote (3" x 0.45")
- cUL listed for dry locations only.

Example:


UDC8 S W40 SR BDIM-W9 SS

- BTRAXW**—Traxon Light Drive (enter quantity): _____
- XP**—Extra power cord (in inches; max. 25 ft.): _____
- XL**—custom lumen reduction (specify lumens): _____


UDC6 — 6 ft.
UDC8 — 8 ft.




S — Separate




SR — Separate Remote




CS — Central Standard



CR — Central Remote




NCR — Nexus Central Remote




BURBANK,
CALIFORNIA,
91505
WWW.
DELRAY
LIGHTING.
COM

6 FT. LED

UDC6.W35



CP DISTRIBUTION



COEFFICIENTS

% CEILING 80	(20% FLOOR)		
% WALL 70	50	30	
0	107	107	107
1	97	93	89
2	88	81	74
3	80	71	63
4	73	62	54
5	67	55	47
6	62	50	41
7	57	45	37
8	53	41	33
9	49	37	29
10	46	34	27

NOTES

UDC6.W35

140W LEDs, 3500°K
 Delivered lumens: 13,014

CRI: 90
 R9 ≥ 72

DOS CIRCULAR REMOTE DRIVERS

Driver must be accessible after installation. For suspended and hard lid ceilings with access panels. Canopy mounts to mud ring attached to J-box.


NOTE: Multiple drivers must be mounted no less than 4 inches apart side-by-side, and 1 inch apart end-to-end, to avoid overheating.

Standard pendant length: 8 ft. Specify **XP** for extra pendant.
 Maximum canopy to fixture distance: 25 ft. Maximum canopy to driver distance: 100 ft. (with 10 AWG wire).




Remote Driver Canopy
 3.8 x 0.45 in.

SR – Separate mount driver installation.



CR – Central mount remote driver installation.




SREM or **CR**EM – Separate or Central Emergency. *T-bar install shown, below.*

Emergency battery pack provides 7W for 90 minutes. (12W also available.)
 Remote install only. Red driver light and test switch mounted in handy box installed at ceiling.

WATTS / LUMENS

Diameter	Watts	Delivered Lumens	Weight
6'	140	13,014	40 lb
8'	188	17,352	50 lb

JOINER



AIRCRAFT CABLE

Note: Aircraft cable suspension not recommended for outdoor use, where fixture will be exposed to water, or subject to wind oscillation. Avoid use near HVAC vents and in environments with corrosive chemical vapors, such as swimming pools.

ACRYLIC DIFFUSER CLEANING

Warning: Do not clean with ammonia based cleaners (e.g. Windex®). Use only water or cleaners specifically formulated for cleaning plastics.

OPTIONS

DIMMING DRIVERS

120/277V, 50/60 Hz.

STANDARD DIMMING

Programmable, 0–10V, dims to 1%.

LUTRON DIMMING DRIVERS

BDIM-W9

- Lutron Hi-Lume L3DA Series, 3-wire
- Dims to 1%

BDIM-W11

- Lutron EcoSystem LDE14 Series
- Dims to 1%
- Fade to off.

RGB OPTIONS

BDMXMOD

- Osram part no. OTDMXRGB supplied.
- DMX control interface for RGB LED.
- Provides DMX control with protocols that meet USITT DMX-512A or DMX512 (DIN 56930-2). No converter is required. DMX controls by others.
- A second 4-conductor control cable to fixture canopy is supplied.

TRAXON LIGHT-DRIVE RGB

(order separately)

BTRAXW—white faceplate

- Standalone, wall-mounted (12V power supply included) DMX controller for RGB LED that provides direct access to fixtures.
- Tune color and brightness with the Light-Drive wheel.
- Fully dimmable white mode button.
- See www.traxon-usa.com for details.

SEPARATE SWITCHING

Control uplight separately from downlight. Order **SS**.