

# ROCKET A-LINE LED OPEN LOWBAY

**DELRAY  
LIGHTING  
INCORPORATED**



**TYPE:**

**PROJECT:**

**ORDER NUMBER:**

Model#	LEDs	Voltage	Dimming	Options
<b>IL7712</b>	<b>W30</b>	<b>1-120V</b>	<b>D11</b>	<b>XP</b> —extra pendant length*
<b>IL7713</b>	<b>W35</b>	<b>2-277V</b>		<b>EM</b> —Emergency
<b>IL7714</b>	<b>W40</b>			<b>I73WG</b> —Wire Guard
<b>IL7716</b>				<b>CMI</b> —Pipe Mount
				<b>BA</b> —Ball Aligner
				<b>RBRD</b> —Red Braided Cord

\*Specify extra pendant length (in inches):

**IL7712/13/14/16**

## CONSTRUCTION

- Spun matte anodized .063 aluminum housing.
- Canopy mounts to standard J-boxes, suspends from aircraft cables with push button gliders.
- Standard mount is 6 ft. adjustable aircraft cable and power cord. Order **XP** for extra pendant length.

## LED DRIVERS

- Standard drivers are constant current, universal voltage, with 0–10V dimming to 15%.
- Emergency Battery Pack (**IL73EM**) provides 7W of power for 90 mins. Voltage must be specified.
- cU.L. listed for damp locations.

## LEDs


- Cree LED modules feature opal diffusers that provide the appearance of an A-lamp from below.
- Available in 30W/2000 lumens, 35W/3000 lumens, 35W/4000 lumens, and 50W/6000 lumens.
- Available in three white color temperatures: **W30** (3000° K), **W35** (3500° K), and **W40** (4000° K).
- CRI = 94, R9 = 72
- Dimming available for all wattages and color temperatures. (See back page for details.)
- 50,000 hour LED life

Specify LED color:

- W30**—White (3000° K)
- W35**—White (3500° K)
- W40**—White (4000° K)


## IL7712 LED

30 watts  
2,000 lumens




## EM

Emergency



## IL7714 LED

35 watts  
4,000 lumens




## IL7716 LED

50 watts  
6,000 lumens


**BURBANK,  
CALIFORNIA,  
91505  
WWW.  
DELRAY  
LIGHTING.  
COM**

## OPEN LOWBAY

### IL7714.W35



## CP DISTRIBUTION



## COEFFICIENTS

% CEILING 80 (20% FLOOR)			
% WALL	70	50	30
0	119	119	119
1	112	109	106
2	105	100	95
3	99	91	85
4	92	83	77
5	87	77	70
6	81	70	63
7	76	65	58
8	71	60	53
9	67	55	48
10	63	51	45

## NOTES

**IL7714.W35**  
 40W 3500° K LEDs  
 Total lumens: 3,938  
 Total luminaire efficacy: 92%

## IL7714 – LED

These LED luminaires that provide conventional footcandle levels  $\leq 1.4\text{W}/\text{FT}^2$ .

Featuring Cree LED modules feature opal diffusers that provide the appearance of an A-lamp from below. Available in three white color temperatures: **W30**, **W35** (3500° K), and **W40** (4000° K); matching the traditional CCT of existing incandescent, and fluorescent lamps. CRI=97, R9=72.

cUL rated for dry locations only.

## LM-79 TEST SUMMARY – IL7306.W35

<b>Driver:</b>	Cree
<b>Total Lumens:</b>	5,896
<b>Input Power (W):</b>	84
<b>Efficacy:</b>	70
<b>Color Rendering Index (CRI):</b>	97

## CREE LMH2 LED MODULE



These modules are durable, field replaceable, and have been Tempo tested by Cree to ensure optimum performance.

## OPTIONS

**D**—standard supplied driver. Programmable, 0–10V, 120/277V, 50/60 Hz, 1% dimming.

### OPTIONAL DRIVER

**BDIM-W11**—Lutron EcoSystem LDE14 Series

- Dims to 1%
- Fade to off
- For 2,000, 3,000 and 4,000 lumen fixtures only.

## HARD STEM

**CM1**— $\frac{1}{2}$ " ID hard stem option, supplied with swivel canopy for earthquake code, sloped ceilings, and indoor areas with light air movement (e.g., near HVAC vents). Pipe replaces power cord and cable. Length must be specified.

Pipe longer than 8 ft. will be shipped in two sections—one 8 ft., the other for the balance—with painted, threaded pipe coupler and set screws. *Not available for metal halide fixtures.*



**NOTE:** Aircraft cable suspension is not recommended for outdoor use, where fixture will be exposed to water, or subject to wind oscillation. Avoid use near HVAC vents and in environments with corrosive chemical vapors, such as swimming pools.

## RED BRAIDED CORD

Red braided power cord. Order **RBRD**.

